





Coelux LS Array


TECHNICAL INFORMATION:

SKYLIGHT SIZE Dimensione dello skylight	498 x 295 mm (x2) 19.6 x 11.6" (x2)
WEIGHT Peso	24 kg 55 lb
NECESSARY SPACE FOR INSTALLATION* Dimensioni minime necessarie	1159 x 500 x 460 mm 45.6 x 19.7 x 18.1"

*dimensions may differ slightly depending on the versions

*le dimensioni possono differire leggermente a seconda delle varianti

	 45°  0.1-100%	 45°  0.1-100%
VERSIONS AVAILABLE Varianti disponibili	On board drivers - included	Remote drivers - on request
POWER INPUT Power input	100-240 V~ 50/60 Hz	4 channels, 450 mA each channel, 42 V DC
POWER CONSUMPTION Consumo energetico	100 W (Max) - 90 W (Typical)	80 W (Max) - 80 W (Typical)
TOTAL LIGHT OUTPUT Emissione luminosa	3000 lm	3000 lm
MODULES Modulo	Head	Head
ORDER CODE CERTIFICATION Codice di ordinazione Certificazione	LS-ARR-HD-3L-DAL-UL UL, FCC LS-ARR-HD-3L-010-UL UL, FCC LS-ARR-HD-3L-DAL-BIS BIS	LS-ARR-HD-3L-DAL-CE CE, CB, PSE LS-ARR-HD-3L-DAL-CCC CCC LS-ARR-HD-3L-DAL-KC KC
MODULES Modulo	Middle	Middle
ORDER CODE CERTIFICATION Codice di ordinazione Certificazione	LS-ARR-MD-3L-DAL-UL UL, FCC LS-ARR-MD-3L-010-UL UL, FCC LS-ARR-MD-3L-DAL-BIS BIS	LS-ARR-MD-3L-CE CE, CB, PSE LS-ARR-MD-3L-CCC CCC LS-ARR-MD-3L-KC KC
MODULES Modulo	Single	Single
ORDER CODE CERTIFICATION Codice di ordinazione Certificazione	LS-ARR-SG-3L-DAL-UL UL, FCC LS-ARR-SG-3L-010-UL UL, FCC LS-ARR-SG-3L-DAL-BIS BIS	LS-ARR-SG-3L-CE CE, CB, PSE LS-ARR-SG-3L-CCC CCC LS-ARR-SG-3L-KC KC



*Inspection hatch: required close to the projector.

*Botola di ispezione: necessaria vicino al proiettore.

